

Top-Care

7227

Maintenance product for windows and front doors for industrial and professional use and for DIY

PRODUCT DESCRIPTION

General

A water-based maintenance product for transparent and opaque coatings; it is water-repellent and protects the surface against contamination. The surface retains its gloss or matt level. Annual maintenance is recommended.

Application area




For the after-care of coated window and exterior door surfaces and garden furniture.

System-matched with Top-Cleaner (7208) in the Window Care-Set (7229) package.

PROCESSING

Processing instructions



- Please shake the product before use.
- The temperature of the product and object, and the room temperature must be at least + 15 °C.
- The optimal conditions for use are between 15 - 25 °C with a relative atmospheric humidity between 40 - 80 %.
- Clean the surfaces beforehand using Top-Cleaner (7208).
- **Front doors and garden furniture:** Apply Top-Care (7227) thinly using a spray bottle and then wipe away with the cloth that is included in the set.
- **Windows:** Spray Top-Care (7227) directly onto the cloth that is included in the set, apply it and then wipe away.
- Avoid intensive rubbing on the surface and do not repolish.
- Please follow our **ARL 304 - Working guideline for coating dimensionally stable and limited dimensionally stable construction elements - Maintenance and repair.**

Application technique



	Wiping
Yield per application (m ² /l)	approx. 40 m ²
Application quantity per application (ml/m ²)	20–30

The shape and surface condition of the workpiece as well as the type of application influence the actual consumption.

ORDERING INFORMATION

Size of trading unit

250 ml


Supplementary products

Top-Cleaner (7208)
Window Care-Set (7229)

Please refer to the corresponding technical data sheets of the products.

FURTHER DETAILS

Durability / storage



Min. 3 year(s) in the original sealed containers.

Make sure the product is protected against moisture, direct sunlight, frost and high temperatures (above 30 °C).

Safety information



Further information on the subject of safety during transport, storage and handling as well as disposal can be found in the relevant safety data sheet. The current version can be accessed on the Internet at www.adler-lacke.com.